



## **Technical Specification**

Product	Code	CMA050
FIGURE	Coue.	CIVIAUSU

Description: 13A Fused Connection Unit With Optional Flex Outlet

FUSE	0			
General Infor	mation			
Plate Dimensior		86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizont	· · /	60.3		
Thate Fixing Centres - Honzon	Style	Rounded Profile		
	Finish	Polar White		
N	laterials	Front Plate & Fuse Drawer: Urea		Rear Housing: Urea
		Terminals: Brass		Terminal Screws: Steel & Yellow Passivated
		Internal Busbars: Formed Pressed	Brass	Earth Strap: Mild Steel
Anti Microbial (	Certified	Yes		
Rated Voltage (V	′~) (Ue)	250		Frequency (Hz) 50
Resistive Load Ra		13		
Fuse Fitted Rating		13A (BS 1362)		
Terminati		Screw		
Terminal Siz		Ø5	Ierminal	Torque Value (Nm) 2
Terminal Capacity - Soli		3 x 2.5 or 2 x 4		
S Twin Earth Te	witched	No Yes		
Product		Fused		
Flex Outlet A		Yes		
Flex Outlet L		Bottom of Plate	Flex Outl	et Dimension (mm) Ø10
Minimum Back Box Dep		25	TION O'UU	
Ingress Pro		IP20		
Operational Temperat		-5 to +40		
Warranty		20		
Standards	BS 1363 BS 1362			
Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.			

UK CA

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com