

Technical Specification



Product Code: CMA203	Dese	cription:	45A 2 Gang (Vertio	cal) Double	Pole Plate Switch Wi	th Neon
OFF ON						
General Informa	ation					
Plate Dimensions		N) x 146 (F	H) x 9.5 (D)			
Plate Fixing Centres - Horizontal (mm)		6	1) X 0.0 (D)			
-	. ,	nded Profi	le			
	-	r White				
Mate	Neoi Term	n Lens: Po iinal Screw	Rocker Switch: Urea olycarbonate vs: Steel & Yellow Pa rs: Formed Pressed		Rear Housing: Urea Terminals: Brass Contacts: Silver "on- Earth Strap: Mild Ste	
Anti Microbial Certified						
Rated Voltage (V~) (Ue)					Frequency (Hz)	50
Resistive Load Rating (A)						
Termination Type		W				
Terminal Size (mm)				Terminal	Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm ²)		6				
Double Pole Switch						
Twin Earth Terminals						
Neon Indi					Indicator Colour	Orange
Product Marking		& Off				
Minimum Back Box Depth (mm)						
Ingress Protection Operational Temperature (°C)		+40				
Warranty (Y	. ,	+40				
	S EN 60669-	1				
Er dia Ba All pr pr A er	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non- enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.					

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (14/09/22) Errors & Omissions excluded. Specification is subject to change without notice.