## Data sheet

## Motion detector



EAN 4007841660215



## **Functional description**

Are you looking for a way to enter the world of motion detectors? The IS 130-2 infrared motion detector is a STEINEL customer favourite of recent years, not meaning that we're resting on our laurels. We've continued to optimise both its design and technology. The sensor classic is the ideal solution for monitoring areas with precision targeting in front of buildings and on driveways. It also provides excellent quality of detection and can be tailored to the specific conditions on site. The motion detector is wired up so easily and quickly, your neighbour won't even notice you installing it.

## **Technical specifications**

Model	Movement sensor
Sensor type	Passive infrared
Detection angle	130° with sneak-by protection
Reach	12 m max.
Application	indoors and outdoors
Installation	Wall
Dimensions(w x h x d):	130 x 78 x 84 mm
Voltage	230-240 V/50 Hz
max. output (electronic ballasts, capacitive, e.g. low-energy lamps)	4 ea. max., C ? 88 μF
Output	max. 600 W, max. 4 Leuchtstofflampen / LED-Leuchtmittel, C<88µF
Capability of masking out individual segments	Yes
Swivelling range	50 °
Tilting range	90 °
Teach-function for response value luminosity	No
Time setting	8 sec 35 min.
Degree of protection (IP)	IP54
Protection class	ll
Temperature	-20-50 °C
Housing	UV-resistant plastic
Version	Black

